





Sping-clamp terminal block 4mm², 2-poles, 1-level, earth connection

Series	HTE
Code	HT250
Type	HTE.4
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	4 mm ²
Connecting capacity	
Flexible wire	0.2-6 mm ²
Rigid wire	0.2-6 mm ²
Wire with ferrule - ferrule type	4 mm ² – WP40/16
Electrical characteristics according to IEC EN standard	
Maximum current (rated cross-section)	–
Caliber	A4
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	–
Section (min-max)	24-10 (AWG)
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	500 V
Operating temperature Min/Max	-40 °C / +80 °C
Insulation stripping length	12 mm
Width (pitch)	6.2 mm
Length	58 mm
Height mounted on TH35-7.5/TH35-15/G32	45 / 52 / – mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	HMT.4/PT/GR (cod. HM251GR)
Blue	–
Thickness	1.5 mm
Cross-connection	
Cross-connection identification strip	PTC/SP (cod. PTC0990)
Coloured partition plate	DFH/1/R (cod. DH01R)
Cross-connection barrier	–
Test plug	SDD/1 (cod. DD001)
Modular test plug	–
End section for modular test plug	–
Marking	
Single marking tag	CNU/8/61 (cod. NU0861S)
Single marking tag for pitch insertion	–
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
DIN rail according to IEC 60715/TH35	PR/3/..
APPROVALS AND MARKINGS	



1 For more details on accessories, refer to the relevant chapters

PRODUCT DESCRIPTION

HTE.4 Sping-clamp terminal block 4mm², 2-poles, 1-level, earth connection