





Sping-clamp terminal block 16mm², 2-poles, 1-level, earth connection

Series	HTE
Code	HT340
Type	HTE.16
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	16 mm ²
Connecting capacity	
Flexible wire	1.5-25 mm ²
Rigid wire	1.5-25 mm ²
Wire with ferrule - ferrule type	16 mm ² – WP160/22
Electrical characteristics according to IEC EN standard	
Maximum current (rated cross-section)	–
Caliber	A7
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	–
Section (min-max)	18-4 (AWG)
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	630 V
Operating temperature Min/Max	-40 °C / +110 °C
Insulation stripping length	18 mm
Width (pitch)	12 mm
Length	80 mm
Height mounted on TH35-7.5/TH35-15/G32	56 / 64 / – mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	HMT.16/PT (cod. HM341GR)
Blue	–
Thickness	1.5 mm
Cross-connection	
Cross-connection identification strip	–
Coloured partition plate	DFH/4/R (cod. DH04R)
Cross-connection barrier	–
Test plug	SDD/1 (cod. DD001)
Modular test plug	–
End section for modular test plug	–
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S)
Single marking tag for pitch insertion	–
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
DIN rail according to IEC 60715/TH35	PR/3/..
APPROVALS AND MARKINGS	



1 For more details on accessories, refer to the relevant chapters

PRODUCT DESCRIPTION

HTE.16 Sping-clamp terminal block 16mm², 2-poles, 1-level, earth connection