




## Screw terminal block 5 x 16 mm<sup>2</sup> + 1 x 25 mm<sup>2</sup> for junction boxes

<b>Series</b>	CONT
<b>Code</b>	CONT616
<b>Type</b>	CONT616
<b>Colour</b>	Transparent
<b>HS code</b>	85369010
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Branch terminal
<b>Rated cross-section</b>	5 x 16 mm <sup>2</sup>
<b>Rated cross-section</b>	1 x 25 mm <sup>2</sup>
<b>Connecting capacity</b>	
<b>N poles</b>	6
<b>Flexible wire</b>	-
<b>Rigid wire</b>	-
<b>Wire with ferrule - ferrule type</b>	-
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	500 V
<b>Maximum current (rated cross-section)</b>	76 A
<b>Caliber</b>	-
<b>Electrical characteristics according to UL Standard</b>	
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Protection degree</b>	IP20
<b>Insulation stripping length</b>	16-21 mm
<b>Dimension</b>	25x9x62x25.25 mm (AxBxCxD)
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polycarbonate UL94V-0
<b>ACCESSORIES</b>	
<b>APPROVALS AND MARKINGS</b>	



\* 2, 3 and 5 poles for quick cabling\* Transparent and self-extinguishing body\* High dielectric strength\* High resistance to chemical and atmospheric agents  
1 IP20 protection degree

## PRODUCT DESCRIPTION

Screw terminal block 5 x 16 mm<sup>2</sup> + 1 x 25 mm<sup>2</sup> for junction boxes