



Screw terminal block 4mm² fuse-holder with 12-48V alarm, 2-levels, grey.color



Series	DSF
Code	DA518GR
Type	DSF.4/GR/C12-48
HS code	85369010
Colour	grey
TECHNICAL FEATURES	
Function/Type	2 levels (fuse-holder + feed-through)
Rated cross-section	4 mm ²
Connecting capacity	
Flexible wire	0.2-6 mm ²
Rigid wire	0.2-6 mm ²
Wire with ferrule - ferrule type	4 mm ² - WP40/16
Characteristics according to European standard IEC EN 60947-7-1 / 60947-7-3	
Maximum voltage AC/DC	800 V
Maximum current (rated cross-section)	6.3 (10 A con CO/5) / 32 A (1)
Caliber	A4
Characteristics according to UL	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	6.3-20 A
Section (min-max)	26-12 (AWG)
Tightening torque value (UL)	4.4 lb.in
Characteristics according to ATEX directive and IEC ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Service temperature Min/Max	-
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	9 mm
Tightening torque value (nom. / max.)	0.5 / 1.2 Nm
Width (pitch)	8 mm
Length	79.5 mm
Height mounted on TH35-7.5/TH35-15/G32	69 / 77 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	DSF.4/PT/GR (cod. DS401GR)
Blue	-
Beige	DSF.4/PT (cod. DS401)
Thickness	1.5 mm
Cross-connection	
Model A)	-
Model B)	-
Rated current carrying capacity IEC/ATEX	-
Cross-connection identification strip	-
Coloured partition plate	DFU/7/R (cod. DU07R)
Cross-connection barrier	-
Test plug socket	-
Test plug	-
Marking	
Snap-on numbering strip	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
Single marking tag	-
Fuse type	5x20 mm (1)
Conductive element	CO/5 (cod. VL103)
Light alarm circuit (110...230 V)	-
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
APPROVALS AND MARKINGS	
	



- * Suitable for 5x20 mm fuses
- * Alarm LED circuit already mounted (12-48 V)
- * Fuse available separately

1 For more details on accessories, refer to the relevant chapters
2 (1) 6.3 A with fuse or 10 A with CO/5 on upper level / 32 A on lower level

PRODUCT DESCRIPTION

DSF.4/GR/C12-48 Screw terminal block 4mm² fuse-holder with 12-48V alarm, 2-levels, grey.color