




Screw

terminal block 10mm² fuse-holder, blown-fuse signal 48V, beige color

Series	SFR – CBF – FPL
Code	FP948
Type	FPL.10/C48
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Fuse-holder 6.3×32 with alarm
Rated cross-section	10 mm ²
Connecting capacity	
Flexible wire	1.5-16 mm ²
Rigid wire	1.5-16 mm ²
Wire with ferrule - ferrule type	10 mm ² – WP100/21
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	800 V
Maximum current (rated cross-section)	10 A
Caliber	B6
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	300 V
Maximum current (rated cross-section)	15 A
Section (min-max)	20-6 (AWG)
Tightening torque value (UL)	7 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	14 mm
Tightening torque value (nom. / max.)	1.2 / 1.9 Nm
Width (pitch)	12 mm
Length	63 mm
Height mounted on TH35-7.5/TH35-15/G32	71 / 79 / 75 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Blue	-
Beige	-
Thickness	-
Cross-connection	
Model A)	-
Model B)	-
Rated current carrying capacity IEC/ATEX	-
Cross-connection identification strip	-
Coloured partition plate	DFU/6/R (cod. DU06R)
Cross-connection barrier	-
Test plug socket	-
Test plug	-
Connection knob	MSM (cod. FC103)
Marking	
Snap-on numbering strip	-
Single marking tag	-
Fuse type	6.3×32 mm (1)
Conductive element	-
Light alarm circuit (12...48 V)	Already mounted
Light alarm circuit (110...230 V)	-
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
APPROVALS AND MARKINGS	





* Suitable for 5x20 mm fuses* Alarm LED circuit already mounted (12-48 V)* Fuse available separately
1 For more details on accessories, refer to the relevant chapters

PRODUCT DESCRIPTION

FPL.10/C48 Screw terminal block 10mm² fuse-holder,
blown-fuse signal 48V, beige color