





Screw terminal block 95mm²,
panel mounting, grey color



Series	GPA
Code	GF100GR
Type	GPA.95/FIX/GR
HS code	85369010
Colour	Grey
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	95 mm ²
Connecting capacity	
Flexible wire	10-95 mm ²
Rigid wire	10-120 mm ²
Wire with ferrule - ferrule type	–
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	1000 V
Maximum current (rated cross-section)	232 A
Caliber	B12
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	232 A
Section (min-max)	2-250 MCM (AWG)
Tightening torque value (UL)	90 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Operating temperature Min/Max	–
ensione impulsiva nom. / grado di inquinamento	12 kV / 3
Insulation stripping length	30 mm
Tightening torque value (nom. / max.)	–
Width (pitch)	26 mm
Length	–
Height mounted on TH35-7.5/TH35-15/G32	–
Height for panel mounting	–
Length mounted on panel	111 mm
Fixing distance between center	97 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
Cross-connection	
Model A)	–
Model B)	–
Rated current carrying capacity IEC/ATEX	–
Multiple cross-connection bar	–
Shunting screw and sleeve (Standard / Exe)	–
Protection cover	–
Coloured partition plate	–
Test plug socket	–
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	–
TH35 snap-fit type	–
TH35 and G32 snap-fit type	–
Mounting rail	
IEC 60715/TH35	–
IEC 60715/G32	–
APPROVALS AND MARKINGS	



* Panel mounting by means of M6 screws

DESCRIZIONE DEL PRODOTTO

GPA.95/FIX/GR
Screw terminal block 95mm2, panel mounting, grey color