




## Screw

terminal block 150mm<sup>2</sup>, panel mounting, beige color

<b>Series</b>	GPA
<b>Code</b>	GF200
<b>Type</b>	GPA.150/FIX
<b>HS code</b>	85369010
<b>Colour</b>	Beige
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Feed-through
<b>Rated cross-section</b>	150 mm <sup>2</sup>
<b>Connecting capacity</b>	
<b>Flexible wire</b>	50-150 mm <sup>2</sup>
<b>Rigid wire</b>	50-185 mm <sup>2</sup>
<b>Wire with ferrule - ferrule type</b>	-
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	1000 V
<b>Maximum current (rated cross-section)</b>	309 A
<b>Caliber</b>	B14
<b>Electrical characteristics according to UL Standard</b>	
<b>Maximum voltage AC/DC</b>	600 V
<b>Maximum current (rated cross-section)</b>	309 A
<b>Section (min-max)</b>	1/0-350 MCM (AWG)
<b>Tightening torque value (UL)</b>	142 lb.in
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Maximum voltage AC/DC</b>	-
<b>Maximum current (rated cross-section)</b>	-
<b>Operating temperature Min/Max</b>	-
<b>ensione impulsiva nom. / grado di inquinamento</b>	12 kV / 3
<b>Insulation stripping length</b>	35 mm
<b>Tightening torque value (nom. / max.)</b>	-
<b>Width (pitch)</b>	31 mm
<b>Length</b>	-
<b>Height mounted on TH35-7.5/TH35-15/G32</b>	
<b>Height for panel mounting</b>	
<b>Lenght mounted on panel</b>	122 mm
<b>Fixing distance between center</b>	106 mm
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>Cross-connection</b>	
<b>Model A)</b>	-
<b>Model B)</b>	-
<b>Rated current carrying capacity IEC/ATEX</b>	-
<b>Multiple cross-connection bar</b>	-
<b>Shunting screw and sleeve (Standard / Exe)</b>	-
<b>Protection cover</b>	-
<b>Coloured partition plate</b>	-
<b>Test plug socket</b>	-
<b>Marking</b>	
<b>Single marking tag</b>	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
<b>End bracket</b>	
<b>TH35 screw type</b>	-
<b>TH35 snap-fit type</b>	-
<b>TH35 and G32 snap-fit type</b>	-
<b>Mounting rail</b>	
<b>IEC 60715/TH35</b>	-
<b>IEC 60715/G32</b>	-
<b>APPROVALS AND MARKINGS</b>	



\* Panel mounting by means of M6 screws

## PRODUCT DESCRIPTION

GPA.150/FIX Screw terminal block 150mm<sup>2</sup>, panel mounting,  
beige color