



High current terminal bolt/bolt
connection 95mm², panel-mountable, grey color



Series	GPM
Code	GP110GR
Type	GPM.95/BB/FIX/GR
HS code	85369010
Colour	Grey
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	95 mm ²
Connecting capacity	
Flexible wire	-
Rigid wire	-
Wire with ferrule - ferrule type	22 mm – M8 (1)
Characteristics according to European standard IEC EN	
Maximum voltage AC/DC	1000 V
Maximum current (rated cross-section)	232 A nom./ 320 A max.
Caliber	-
Characteristics according to ATEX directive and IEC ex standard	
Maximum voltage AC/DC	630 V
Maximum current (rated cross-section)	232 A
Service temperature Min/Max	-40 °C / +80 °C
ensione impulsiva nom. / grado di inquinamento	12 kV / 3
Insulation stripping length	-
Tightening torque value (nom. / max.)	6 / 9 Nm
Width (pitch)	32 mm
Length	-
Height mounted on TH35-7.5/TH35-15/G32	- / - / -
Height for panel mounting	76 mm
Lenght mounted on panel	176 mm
Fixing distance between center	158 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
Cross-connection	
Model A)	POF/95/... (cod. P095...)
Rated current carrying capacity IEC/ATEX	232 A / 232 A
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	PR/DIN/...
APPROVALS AND MARKINGS	



* Panel mount version - M6 screws (recommended with screwdriver and washer slot)
* Parallel cross connection available

1 For more details on accessories, refer to the relevant chapters
2 (1) Larghezza barra / diametro bullone

PRODUCT DESCRIPTION

GPM.95/BB/FIX/GR

High current terminal bolt/bolt connection 95mm², panel-mountable, grey color