


High current terminal
screw/screw connection 150mm², panel-mountable, grey color

Series	GPM
Code	GP610GR
Type	GPM.150/CC/FIX/GR
HS code	85369010
Colour	Grey
TECHNICAL FEATURES	
Function/Type	Feed-through
Rated cross-section	150 mm ²
Connecting capacity	
Flexible wire	50-150 mm ²
Rigid wire	35-185 mm ²
Wire with ferrule - ferrule type	-
Characteristics according to European standard IEC EN	
Maximum voltage AC/DC	1000 V
Maximum current (rated cross-section)	309 A
Caliber	B14
Characteristics according to UL	
Characteristics according to ATEX directive and IEC ex standard	
Maximum voltage AC/DC	1000 V
Maximum current (rated cross-section)	309 A
Service temperature Min/Max	-40 °C / +80 °C
Rated impulse withstand voltage / pollution degree	12 kV / 3
Insulation stripping length	35 mm
Tightening torque value (nom. / max.)	10 / 15 Nm
Width (pitch)	42 mm
Length	-
Height mounted on TH35-7.5/TH35-15/G32	- / - / -
Height for panel mounting	129 mm
Length mounted on panel	173 mm
Fixing distance between center	158 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
Cross-connection	
Model A)	PFX/150/... (cod. PX15...)
Rated current carrying capacity IEC/ATEX	309 A / 309 A
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	PR/DIN/...
APPROVALS AND MARKINGS	



* Panel mount version - M6 screws (recommended with screwdriver and washer slot)
* Parallel cross connection available

1 For more details on accessories, refer to the relevant chapters

PRODUCT DESCRIPTION

GPM.150/CC/FIX/GR
High current terminal screw/screw connection 150mm², panel-mountable, grey

color