


Disconect terminal board for
voltage-current measures, black cover



Series	MZ
Code	MZ300N
Type	MS/8x10/N
HS code	85369010
Colour	Green
TECHNICAL FEATURES	
Function/Type	Sectioning and measurement
Rated cross-section	6 mm ²
Rated cross-section	
Connecting capacity	
Flexible wire	0.5-16 mm ²
Rigid wire	-
Wire with ferrule - ferrule type	-
Characteristics according to European standard IEC EN	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	41 A
Caliber	-
Characteristics according to UL	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	-
Characteristics according to ATEX directive and IEC ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Service temperature Min/Max	-
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	-
Tightening torque value (nom. / max.)	1.2 Nm
Dimension	112x112x65 mm (AxBxH)
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	-
Insulated bushing	-
APPROVALS AND MARKINGS	



- * 8-poles, 4 amperometric and 4 voltmetric
- * Polycarbonate, filled with fibreglass, insulated body
- * Metal parts in copper-zinc alloy with nickel plating
- * Black polyamide cover

1 (1) Altezza con coperchio e con viti di fissaggio

PRODUCT DESCRIPTION

MS/8X10/N
Disconect terminal board for voltage-current measures, black cover