



**Disconenct**

terminal board for voltage-current measures, transparent cover

<b>Series</b>	<b>MZ</b>
<b>Code</b>	<b>MZ300T</b>
<b>Type</b>	<b>MS/8x10/T</b>
<b>HS code</b>	<b>85369010</b>
<b>Colour</b>	<b>Green</b>
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Sectioning and measurement
<b>Rated cross-section</b>	6 mm <sup>2</sup>
<b>Rated cross-section</b>	
<b>Connecting capacity</b>	
<b>Flexible wire</b>	0.5-16 mm <sup>2</sup>
<b>Rigid wire</b>	–
<b>Wire with ferrule - ferrule type</b>	–
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	500 V
<b>Maximum current (rated cross-section)</b>	41 A
<b>Caliber</b>	–
<b>Electrical characteristics according to UL Standard</b>	
<b>Maximum voltage AC/DC</b>	–
<b>Maximum current (rated cross-section)</b>	–
<b>Section (min-max)</b>	–
<b>Tightening torque value (UL)</b>	–
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Maximum voltage AC/DC</b>	–
<b>Maximum current (rated cross-section)</b>	–
<b>Operating temperature Min/Max</b>	–
<b>Rated impulse withstand voltage / pollution degree</b>	6 kV / 3
<b>Insulation stripping length</b>	–
<b>Tightening torque value (nom. / max.)</b>	1.2 Nm
<b>Dimension</b>	112x112x65 mm (AxBxH)
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	–
<b>Insulated bushing</b>	–
<b>APPROVALS AND MARKINGS</b>	



\* 8-poles, 4 amperometric and 4 voltmetric\* Polycarbonate, filled with fibreglass, insulated body\* Metal parts in copper-zinc alloy  
 1 (1) Altezza con coperchio e con viti di fissaggio

**DESCRIZIONE DEL PRODOTTO**

MS/8X10/T Disconenct terminal board for voltage-current measures, transparent cover