




distribution terminal board unipolar, 12 x 10 mm<sup>2</sup>, blue

Series	QBLOK
Code	QBLOK1201
Type	QBLOK.12/BLU
HS code	85369010
Colour	Blue
<b>TECHNICAL FEATURES</b>	
Function/Type	Distribution terminal board
Number and rated cross connection	
A	
B	
C	
D	-
Input A	
Rated cross-section	12 x 10 mm <sup>2</sup>
Connecting capacity (flexible)	1.5-10 mm <sup>2</sup>
Connecting capacity (rigid)	1.5-16 mm <sup>2</sup>
Connecting capacity (with ferrule)	10 mm <sup>2</sup> - WP 100/21
Supply bar dimension	
Output B	
Rated cross-section	-
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Output C	
Rated cross-section	-
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
Output D	
Rated cross-section	-
Connecting capacity (flexible)	-
Connecting capacity (rigid)	-
Connecting capacity (with ferrule)	-
<b>Electrical characteristics according to IEC EN standard</b>	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	63 A
Caliber	B5
<b>Electrical characteristics according to UL Standard</b>	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	-
Short term current allowed (I <sub>cw</sub> ) (value effective for 1s)	-
Peak current (I <sub>pk</sub> )	-
Rated impulse withstand voltage / pollution degree	-
Insulation stripping length	6 mm
Tightening torque value (nom. / max.)	2 / 2.5 Nm
Plastic material	Polyamide UL94V-0
Width (pitch)	16 mm
Length	85 mm
Height mounted on TH35-7.5/TH35-15	33 / 41 mm
Height for panel mounting	
<b>ACCESSORIES</b>	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S)
Marking tag	
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
<b>Mounting rail</b>	
DIN rail according to IEC 60715/TH35	-
IEC 60715/TH35	PR/3/...
<b>APPROVALS AND MARKINGS</b>	



## DESCRIZIONE DEL PRODOTTO

distribution terminal board unipolar, 12 x 10 mm<sup>2</sup>, blue