




Single-pole terminal block 12x10mm², blue

| | |
|--|-----------------------------------|
| Series | QBLOK |
| Code | QBLOK1201 |
| Type | QBLOK.12/BLU |
| HS code | 85369010 |
| Colour | Blue |
| TECHNICAL FEATURES | |
| Function/Type | Screw Distribution terminal board |
| Number and rated cross connection | |
| A | 12 x 10 mm ² |
| B | – |
| C | – |
| D | – |
| Input A | |
| Rated cross-section | 12 x 10 mm ² |
| Connecting capacity (flexible) | 1.5–10 mm ² |
| Connecting capacity (rigid) | 1.5–16 mm ² |
| Connecting capacity (with ferrule) | 10 mm ² – WP 100/21 |
| Supply bar dimension | – |
| Output B | |
| Rated cross-section | – |
| Connecting capacity (flexible) | – |
| Connecting capacity (rigid) | – |
| Connecting capacity (with ferrule) | – |
| Output C | |
| Rated cross-section | – |
| Connecting capacity (flexible) | – |
| Connecting capacity (rigid) | – |
| Connecting capacity (with ferrule) | – |
| Output D | |
| Rated cross-section | – |
| Connecting capacity (flexible) | – |
| Connecting capacity (rigid) | – |
| Connecting capacity (with ferrule) | – |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 500 V |
| Maximum current (rated cross-section) | 63 A |
| Caliber | B5 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | – |
| Maximum current (rated cross-section) | – |
| Section (min-max) | – |
| Tightening torque value (UL) | – |
| Short term current allowed (I _{cw}) (value effective for 1s) | – |
| Peak current (I _{pk}) | – |
| Rated impulse withstand voltage / pollution degree | – |
| Insulation stripping length | 6 mm |
| Tightening torque value (nom. / max.) | 2 / 2.5 Nm |
| Plastic material | Polyamide UL94V-0 |
| Width (pitch) | 16 mm |
| Length | 85 mm |
| Height mounted on TH35-7.5/TH35-15 | 33 / 41 mm |
| Height for panel mounting | – |
| ACCESSORIES | |
| Marking | |
| Single marking tag | CNU/8/51 (cod. NU0851S) |
| Marking tag | – |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| Mounting rail | |
| DIN rail according to IEC 60715/TH35 | – |
| IEC 60715/TH35 | PR/3/... |
| APPROVALS AND MARKINGS | |
| | Ⓢ, |



- * IP20 protection degree
- * Marking possible with a CNU/8 or CNU/10 tag
- * Available in grey, green and blue colors
- * Self-extinguishing plastic material: UL94V-0
- * Protected against accidental contact

1 For more details, refer to the data sheet

PRODUCT DESCRIPTION

QBLOK.12/BLU Single-pole terminal block 12x10mm², blue