Single-pole terminal block

12x10mm2, grey

Series	QBLOK
Code	QBLOK1203
Type	QBLOK.12/GR
HS code	85369010
Colour	Grey
TECHNICAL FEATURES	
Function/Type	
Number and rated cross connection	
A	
B	
C	
D	–
Input A	
Rated cross-section	12 x 10 mm²
Connecting capacity (flexible)	1.5–10 mm²
Connecting capacity (rigid)	1.5–16 mm²
Connecting capacity (with ferrule)	10 mm² – WP 100/21
Supply bar dimension	
Output B	
Rated cross-section	–
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Output C	
Rated cross-section	–
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Output D	
Rated cross-section	–
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	63 A
Caliber	B5
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Section (min-max)	–
Tightening torque value (UL)	–
Short term current allowed (Icw) (value effective for 1s)	
Peak current (Ipk)	
Rated impulse withstand voltage / pollution degree	–
Insulation stripping length	6 mm
Tightening torque value (nom. / max.)	2 / 2.5 Nm
Plastic material	Polyamide UL94V-0
Width (pitch)	16 mm
Length	85 mm
Height mounted on TH35-7.5/TH35-15	33 / 41 mm
Height for panel mounting	–
ACCESSORIES	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S)
Marking tag	–
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
DIN rail according to IEC 60715/TH35	–
IEC 60715/TH35	PR/3/…
APPROVALS AND MARKINGS	⑭,

* IP20 protection degree* Marking possible with a CNU/8 or CNU/10 tag* Available in grey, green and blue colors* Self-extinguishing plastic material: UL94V-0* Protected against accidental contact
1 For more details, refer to the data sheet

PRODUCT DESCRIPTION

QBLOK.12/GR
Single-pole terminal block 12x10mm2, grey