

4-poles terminal block 160A with 14 holes, B.U. version



Series	QBLOK
Code	QBLOK4161U
Type	QBLOK4P160A14-U
HS code	85369010
Colour	Grey
TECHNICAL FEATURES	
Function/Type	Distribution terminal board
Number and rated cross connection	Values for each bar
A	1 x 50 mm ²
B	4 x 35 mm ²
C	9 x 16 mm ²
D	–
Input A	1 x 50 mm ²
Rated cross-section	50 mm ²
Connecting capacity (flexible)	10-50 mm ²
Connecting capacity (rigid)	10-50 mm ²
Connecting capacity (with ferrule)	35 mm ² – WP 350/30
Supply bar dimension	–
Output B	4 x 35 mm ²
Rated cross-section	35 mm ²
Connecting capacity (flexible)	10-35 mm ²
Connecting capacity (rigid)	10-35 mm ²
Connecting capacity (with ferrule)	25 mm ² (WP 250/29)
Output C	9 x 16 mm ²
Rated cross-section	16 mm ²
Connecting capacity (flexible)	2.5-16 mm ²
Connecting capacity (rigid)	2.5-16 mm ²
Connecting capacity (with ferrule)	16 mm ² (WP 160/22)
Output D	–
Rated cross-section	–
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	160 A
Caliber	–
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Section (min-max)	–
Tightening torque value (UL)	–
Short term current allowed (Icw) (value effective for 1s)	6 kA
Peak current (Ipk)	38 kA
Rated impulse withstand voltage / pollution degree	8kV / 3
Insulation stripping length	13 mm
Tightening torque value (nom. / max.)	2 / 2.5 Nm
Plastic material	Polyamide, polycarbonate
Width (pitch)	181 mm
Length	99 mm
Height mounted on TH35-7.5/TH35-15	–
Height for panel mounting	53 mm
ACCESSORIES	
Marking	–
Single marking tag	CNU/8/51 (cod. NU0851S)
Marking tag	–
End bracket	–
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	–
DIN rail according to IEC 60715/TH35	–
IEC 60715/TH35	PR/3/...
APPROVALS AND MARKINGS	
	



PRODUCT DESCRIPTION

QBLOK4P160A14-U 4-poles terminal block 160A with 14 holes, B.U. version