



unipolar distribution terminal boards, 2 x 2.0 mm<sup>2</sup>, grey

Series	POLM
Code	QPOL1203
Type	POLM.1215
HS code	85369010
Colour	Grey
<b>TECHNICAL FEATURES</b>	
Function/Type	Distribution terminal board
Input A	
Rated cross-section	2 x 2.0 mm <sup>2</sup>
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Output B	
Rated cross-section	12 x 1.5 mm <sup>2</sup>
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Output C	
Rated cross-section	1 x 1.0 mm <sup>2</sup>
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Output D	
Rated cross-section	–
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
<b>Electrical characteristics according to IEC EN standard</b>	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	80 A
Caliber	–
<b>Electrical characteristics according to UL Standard</b>	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Section (min-max)	–
Tightening torque value (UL)	–
Rated impulse withstand voltage / pollution degree	–
Insulation stripping length	–
Tightening torque value (nom. / max.)	–
Plastic material	Polyamide
Width (pitch)	–
Length	–
Height mounted on TH35-7.5/TH35-15	– / –
<b>ACCESSORIES</b>	
<b>Marking</b>	
Single marking tag	–
<b>End bracket</b>	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BT0 (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
<b>Mounting rail</b>	
IEC 60715/TH35	PR/3/...
<b>APPROVALS AND MARKINGS</b>	



## DESCRIZIONE DEL PRODOTTO

unipolar distribution terminal boards, 2 x 2.0 mm<sup>2</sup>, grey