




Single-pole terminal block
2x2.0mm², green (discontinued)

Series	POLM
Code	QPOL1204
Type	POLM.1215/TE
Colour	Green
TECHNICAL FEATURES	
Function/Type	Distribution terminal board
Input A	
Rated cross-section	2 x 2.0 mm ²
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Output B	
Rated cross-section	12 x 1.5 mm ²
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Output C	
Rated cross-section	1 x 1.0 mm ²
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Output D	
Rated cross-section	–
Connecting capacity (flexible)	–
Connecting capacity (rigid)	–
Connecting capacity (with ferrule)	–
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	80 A
Caliber	–
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Section (min-max)	–
Tightening torque value (UL)	–
Rated impulse withstand voltage / pollution degree	–
Insulation stripping length	–
Tightening torque value (nom. / max.)	–
Plastic material	Polyamide
Width (pitch)	–
Length	–
Height mounted on TH35-7.5/TH35-15	– / –
ACCESSORIES	
Marking	
Single marking tag	–
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
APPROVALS AND MARKINGS	



* DIN rail and panel mountable

DESCRIZIONE DEL PRODOTTO

POLM.1215/TE
single-pole terminal block 2x2.0mm², green (discontinued)