


Type	SFR.4	CBF.4
Voltage (V)	250	250
Current (A)	6.3	6.3/10 max.
PROTECTION AGAINST OVERLOAD AND SHORT CIRCUIT		
Single configuration (In)	2.5W	2.5W
Composite configuration (In)	15.24W	16.24W
PROTECTION AGAINST SHORT CIRCUIT		
Single configuration (In)	0W	0W
Composite configuration (In)	15.24W	15.24W
Single configuration (In)	2.5W	2.5W
Composite configuration (In)	15.24W	16.24W

Screw terminal block 4mm² fuse-holder, 1-level, blue color

Series	SFR – CBF
Code	SF850
Type	SFR.4 (Ex)i
HS code	85369010
Colour	blue
TECHNICAL FEATURES	
Function/Type	Fuse-holder 5x20
Rated cross-section	4 mm ²
Connecting capacity	
Flexible wire	0.2-6 mm ²
Rigid wire	0.2-6 mm ²
Wire with ferrule - ferrule type	4 mm ² – WP40/16
Characteristics according to European standard IEC EN 60947-7-1 / 60947-7-3	
Maximum voltage AC/DC	800 V
Maximum current (rated cross-section)	6.3 A (20 A con CO/5) (1)
Caliber	A4
Characteristics according to UL	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	6.3 A
Section (min-max)	20-12 (AWG)
Tightening torque value (UL)	4.4 lb.in
Characteristics according to ATEX directive and IEC ex standard	
Maximum voltage AC/DC	–
Maximum current (rated cross-section)	–
Service temperature Min/Max	–
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	11 mm
Tightening torque value (nom. / max.)	0.5 / 1.2 Nm
Width (pitch)	8 mm
Length	52 mm
Height mounted on TH35-7.5/TH35-15/G32	52 / 60 / 56 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	SFR.4/PT/GR (cod. SF701GR)
Blue	SFR.4/PT (Ex)i (cod. SF801)
Beige	SFR.4/PT (cod. SF701)
Thickness	1.5 mm
Cross-connection	
Model A)	–
Model B)	–
Rated current carrying capacity IEC/ATEX	–
Cross-connection identification strip	–
Coloured partition plate	DFU/3/R (cod. DU03R)
Cross-connection barrier	–
Test plug socket	–
Test plug	–
Marking	
Snap-on numbering strip	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
Single marking tag	–
Fuse type	5x20 mm (1)
Conductive element	CO/5 (cod. VL103)
Light alarm circuit (12...48 V)	CIL/12-24-48 (cod. SF518)
Light alarm circuit (110...230 V)	CIL/115-230 (cod. SF510)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	–
APPROVALS AND MARKINGS	



- * Suitable for 5x20 mm fuses
- * Accessory with alarm LED, available separately
- * Can be use as disconnecter, using the accessory, to be inserted in place of the fuse

1 For more details on accessories, refer to the relevant chapters
2 (1) 6.3 A with fuse or 20 A with CO/5

PRODUCT DESCRIPTION

SFR.4(Ex)l Screw terminal block 4mm² fuse-holder, 1-level, blue color