




SCHEDA TECNICA DI RIFERIMENTO PER IL PRODOTTO									
Modello	Descrizione	Materiali	Dimensioni	Caratteristiche	Condizioni d'uso	Temperatura	Pressione	Velocità	Altitudine
T0320	Terminali a vite per terra	Plastica	16 mm	35 mm²	IEC 60715	130 °C	1000 hPa	10 m/s	1000 m

screw terminal block 1 level earth connection, 35 mm²

Series	TEC
Code	T0320
Type	TEC.35/0
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	35 mm²
Connecting capacity	
Flexible wire	2.5-50 mm²
Rigid wire	2.5-50 mm²
Wire with ferrule - ferrule type	-
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Caliber	B9
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	-
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Rated impulse withstand voltage / pollution degree	12 kV / 3
Insulation stripping length	18 mm
Tightening torque value (nom. / max.)	2.5 / 5 Nm
Width (pitch)	16 mm
Length	56 mm
Height mounted on TH35-7.5/TH35-15/G32	63 / 71 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Green	-
Thickness	-
Cross-connection	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BT0 (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
APPROVALS AND MARKINGS	



DESCRIZIONE DEL PRODOTTO

screw terminal block 1 level earth connection, 35 mm²