


SERIE T0810 - 2 BLOCCHI TERMINALI PER TERRAZIONE			
DESCRIZIONE	TEC.70/O	TEC.70/O	TEC.70/O
NUMERO DI TERMINALI	2	2	2
SEZIONE MINIMA	10-95 mm ²	10-95 mm ²	10-95 mm ²
SEZIONE MASSIMA	10-95 mm ²	10-95 mm ²	10-95 mm ²
ALTEZZA MONTATA SU RAIL	81.5 / 74 / - mm	81.5 / 74 / - mm	81.5 / 74 / - mm
INDICE DI TEMPERATURA DEL MATERIALE	130 °C	130 °C	130 °C
INDICE DI TEMPERATURA DI GIUNTA	130 °C	130 °C	130 °C
INDICE DI TEMPERATURA DI CAVITÀ	130 °C	130 °C	130 °C
INDICE DI TEMPERATURA DI SUPERFICIE	130 °C	130 °C	130 °C
INDICE DI TEMPERATURA DI AMBIENTE	130 °C	130 °C	130 °C
INDICE DI TEMPERATURA DI CAVITÀ	130 °C	130 °C	130 °C
INDICE DI TEMPERATURA DI SUPERFICIE	130 °C	130 °C	130 °C
INDICE DI TEMPERATURA DI AMBIENTE	130 °C	130 °C	130 °C

Screw terminal block 70mm2,1-level, earth connection, for TH35 rail

Series	TEC
Code	T0810
Type	TEC.70/O
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Ground terminal blocks
Rated cross-section	70 mm ²
Connecting capacity	
Flexible wire	10-95 mm ²
Rigid wire	10-95 mm ²
Wire with ferrule - ferrule type	-
Characteristics according to European standard IEC EN 60947-7-2	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Caliber	B11
Characteristics according to UL	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	-
Characteristics according to ATEX directive and IEC ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Service temperature Min/Max	-
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	25 mm
Tightening torque value (nom. / max.)	6 / 9 Nm
Width (pitch)	20.5 mm
Length	70 mm
Height mounted on TH35-7.5/TH35-15/G32	81.5 / 74 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Green	-
Thickness	-
Cross-connection	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
APPROVALS AND MARKINGS	



* Same profile and dimensions of the corresponding terminals of the CBC and GPA series
* No end plates required, already closed in yellow/green shells

PRODUCT DESCRIPTION

TEC.70/O Screw terminal block 70mm2,1-level, earth connection, for TH35 rail

