


Spring.Clamp terminal block 2.poli 4mm2 for junction boxes

<b>Series</b>	UC
<b>Code</b>	UC02
<b>Type</b>	UC02
<b>Colour</b>	Transparent
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Branch terminal
<b>Rated cross-section</b>	4 mm <sup>2</sup>
<b>Connecting capacity</b>	
<b>N poles</b>	2
<b>Flexible wire</b>	0.34-4 mm <sup>2</sup>
<b>Rigid wire</b>	0.2-4 mm <sup>2</sup>
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	450 V
<b>Maximum current (rated cross-section)</b>	32 A
<b>Caliber</b>	-
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Protection degree</b>	IP20
<b>Insulation stripping length</b>	11 mm
<b>Dimension</b>	13 x 21 x 11 mm (AxBxC)
<b>Insulation material temperature index (EN 60216-1)</b>	85 °C
<b>Plastic material</b>	Polycarbonate UL94V-0
<b>ACCESSORIES</b>	
<b>APPROVALS AND MARKINGS</b>	



- \* Compact dimension
- \* Screwdriver is not required, thanks to the integrated lever
- \* Transparent body

1 IP20 protection degree

**PRODUCT DESCRIPTION**

Spring.Clamp terminal block 2.poli 4mm2 for junction boxes