



1 solid state relay 24Vdc transistor
500mA screw, fixed



Series	
Code	X766083
Type	CWOT 6-2083 (1)
INPUT TECHNICAL DATA	
Input rated voltage	24 Vdc (range 10...40 Vdc)
Pull in / drop out voltage type	5 V / 5 V
Current consumption	6 mA $\pm$ 10% at 24 Vdc
Turn ON / OFF time	12 μ s / 12 μ s
Frequency	1 KHz
Protection circuit	Free-wheel diode
Connection terminal	2.5 mm ² screw
Input channels	1 not pluggable
OUTPUT TECHNICAL DATA	
Contact type	transistor (2)
Output voltage	5...48 Vdc
Nominal current	10...500 mA (24 Vdc)
Connection type	
Protection circuit device	suppressor diode
GENERAL TECHNICAL DATA	
Operating temperature range	-25...+60°C
Input / output isolation	3.5 kVac / 60 s
Protection degree	IP 20
Overvoltage category / pollution degree	II / 2
Status indication	LED "Input"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	84x79x6.2 mm
Approximate weight	29 g
Mounting information	on a rail, side by side
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
APPROVALS AND MARKINGS	CE,



DESCRIZIONE DEL PRODOTTO

Solid state relay modules single channel, input rated: 24 Vdc (range 10...40 Vdc), input channels: 1 not pluggable, contact type: transistor (2)