




1 electromechanical relay
24Vac/dc SPDT 6A, screw, pluggable

Series	CWR
Code	X766842
Type	CWRE7-0842
HS code	85364190
INPUT TECHNICAL DATA	
Input rated voltage	24 Vac/dc $\pm 10\%$
Pull in / drop out voltage type	18 V / 1.2 V
Current consumption	7 mA $\pm 10\%$
Turn ON / OFF time	8 ms / 5 ms
Protection circuit	Free-wheel diode, Reverse polarity
Connection terminal	2.5 mm ² screw
Input channels	1 pluggable
OUTPUT TECHNICAL DATA	
Contact type	SPDT, 1 form C, AgSnO ₂
Output voltage	400 Vac max., 30 Vdc max.
Nominal current	6 A (250 Vac), 6 A (30 Vdc)
Connection type	
GENERAL TECHNICAL DATA	
Operating temperature range	-20...+70°C
Input / output isolation	4 kVac / 60 s
Protection degree	IP 20
Overvoltage category / pollution degree	II / 2
Status indication	LED "Input"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	6.2x89x77 mm
Approximate weight	35 g
Mounting information	on a rail, side by side
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Marking tag	NUPUTUK50
Spare part relay	8904027
Plugin jumper	CWBK7-0813 (20 poles)
APPROVALS AND MARKINGS	CE, 



* Pluggable relay* AC/DC input voltage* SPDT contact* Compact dimensions* Available plug-in jumper for potential distribution
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

DESCRIZIONE DEL PRODOTTO

CWRE7-0842 1
electromechanical relay 24Vac/dc SPDT 6A, screw, pluggable