


## 1 electromechanical relay 115Vac/dc SPDT 6A, screw, pluggable

|  |  |
|--|--|
| <b>Series</b>                                  | CWR                                      |
| <b>Code</b>                                    | X766846                                  |
| <b>Type</b>                                    | CWRE7-0846                               |
| <b>HS code</b>                                 | 85366990                                 |
| <b>INPUT TECHNICAL DATA</b>                    |  |
| <b>Input rated voltage</b>                     | 115 Vac/dc $\pm 10\%$                    |
| <b>Current consumption</b>                     | 4 mA $\pm 10\%$                          |
| <b>Turn ON / OFF time</b>                      | 8 ms / 5 ms                              |
| <b>Protection circuit</b>                      | Free-wheel diode, Reverse polarity       |
| <b>Connection terminal</b>                     | 2.5 mm <sup>2</sup> screw                |
| <b>Input channels</b>                          | 1 pluggable                              |
| <b>OUTPUT TECHNICAL DATA</b>                   |  |
| <b>Contact type</b>                            | SPDT, 1 form C, AgSnO <sub>2</sub>       |
| <b>Output voltage</b>                          | 400 Vac max., 30 Vdc max.                |
| <b>Nominal current</b>                         | 6 A (250 Vac), 6 A (30 Vdc)              |
| <b>Connection type</b>                         | 2.5 mm <sup>2</sup> screw type           |
| <b>GENERAL TECHNICAL DATA</b>                  |  |
| <b>Operating temperature range</b>             | -20...+70°C                              |
| <b>Input / output isolation</b>                | 4 kVac / 60 s                            |
| <b>Protection degree</b>                       | IP 20                                    |
| <b>Overvoltage category / pollution degree</b> | II / 2                                   |
| <b>Status indication</b>                       | LED "Input"                              |
| <b>Housing material</b>                        | UL94V-0 plastic material                 |
| <b>Dimensions (LxHxD)</b>                      | 6.2x89x77 mm                             |
| <b>Approximate weight</b>                      | 35 g                                     |
| <b>Mounting information</b>                    | on a rail, side by side                  |
| <b>ACCESSORIES</b>                             |  |
| <b>Mounting rail (IEC60715/TH35-7.5)</b>       | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| <b>Marking tag</b>                             | NUPUTUK50                                |
| <b>Plugin jumper</b>                           | CWBK7-0813 (20 poles)                    |
| <b>APPROVALS AND MARKINGS</b>                  | CE,                                      |



- \* Pluggable relay
- \* AC/DC input voltage
- \* SPDT contact
- \* Compact dimensions
- \* Available plug-in jumper for potential distribution

1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

### PRODUCT DESCRIPTION

CWRE7-0846 1 electromechanical relay 115Vac/dc SPDT 6A, screw, pluggable