



3-phase power supply input 400-500Vac / output 24Vdc 20A



Series	Triple Power
Code	XCSG481C
Type	CSG481C (1)
HS code	85044083
INPUT TECHNICAL DATA	
Input rated voltage	3x 400–500 Vac
Input voltage AC	340...550 Vac
Frequency	47...63 Hz
Current consumption	1.2 A (400 Vac) / 0.8 A (500 Vac)
Inrush peak current	40 A
Power factor	> 0.95
External protection on AC line	MT: C-6 A / Fuse: T-6.3 A
OUTPUT TECHNICAL DATA	
Output voltage range	24 Vdc ±1%
Output adjustable range	23.3...27.5 Vdc
Continuous current	20 A at 45°C
Overload limiting	28 A for >5 s
Short circuit peak current	50 A for 0.3 s
Ripple @ nominal ratings	100 mVpp
Hold up time	50 ms (400 Vac) / 50 ms (500 Vac)
Status indication	LED "DC OK"
Alarm contact	dry contact, max. 1A @ 24 Vdc (Uout >21.6 Vdc)
Parallel connection	possible
Redundant parallel connection	possible with external ORing diode
GENERAL TECHNICAL DATA	
Efficiency	93% (400 Vac) / 92% (500 Vac)
Dissipated power	36 W (400 Vac) / 42 W (500 Vac)
Operating temperature range	-20...+60°C (derating -16 W >45°C)
Input / output isolation	3 kVac / 60 s (SELV output)
Input / ground isolation	2 kVac / 60 s
Output / ground isolation	0.5 kVac / 60 s
Safety Standard	EN 60950-1
EMC Standard	EN 61000-6-2, EN 61000-6-4
Overvoltage category / pollution degree	II / 2
Protection degree	IP 20
Connection terminal	2.5 mm ² / 2.5 mm ²
Housing material	aluminium
Dimensions (LxHxD)	73x137x140 mm
Approximate weight	1 kg
Mounting information	vertical on a rail, 10 mm from adjacent components
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
APPROVALS AND MARKINGS	CE,



* 3-phase 400-500 Vac input or 2-phase with derating* Short circuit, overload, input and output overvoltage protections* Over temperature protection* Suitable for applications that require high reliability and performance* Smart alarm contact, signals when output voltage drops more than 10%* High overload capability to ensure the protections selectivity and start-up of heavy loads
 1 Please refer to the datasheet for more details
 2 Above overcurrent limit, the protection starts cycling in ON/OFF mode (hiccup autoreset), the maximum current supplied depends by the line resistance
 3 (1) discontinued product, replaced by XCSL3480W024VAA

PRODUCT DESCRIPTION

CSG481C 3-phase power supply input 400-500Vac / output 24Vdc 20A