



3-phase power supply input 400-500Vac / output 72Vdc 13.3A



Series	Triple Power
Code	XCSG960G
Type	CSG960G
HS code	85044083
INPUT TECHNICAL DATA	
Input rated voltage	3x 400–500 Vac
Input voltage AC	340...550 Vac
Frequency	47...63 Hz
Current consumption	2.2 A (400 Vac) / 1.1 A (500 Vac)
Inrush peak current	20 A
Power factor	> 0.65
External protection on AC line	MT: C-10 A / Fuse: T 10 A
OUTPUT TECHNICAL DATA	
Output voltage range	72 Vdc
Output adjustable range	72...85 Vdc
Continuous current	13.3 A at 50°C
Overload limiting	17 A for >5 s
Short circuit peak current	27 A for 5 s
Ripple @ nominal ratings	100 mVpp
Hold up time	15 ms (400 Vac) / 18 ms (500 Vac)
Status indication	LED "DC OK" / LED "Alarm"
Alarm contact	dry contact, max. 1A @ 24 Vdc (Uout >68.4 Vdc)
Parallel connection	possible
Redundant parallel connection	already fitted with internal ORing diode
GENERAL TECHNICAL DATA	
Efficiency	94% (400 Vac) / 94% (500 Vac)
Dissipated power	60 W (400 Vac) / 60 W (500 Vac)
Operating temperature range	-20...+60°C (derating -18 W >45°C)
Input / output isolation	3 kVac / 60 s (no SELV output)
Input / ground isolation	2 kVac / 60 s
Output / ground isolation	0.5 kVac / 60 s
Safety Standard	EN 62368-1, UL508
EMC Standard	EN 61000-3-2, EN 61000-3-3, EN 61000-4-11, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-6-2, EN 61000-6-4
Overvoltage category / pollution degree	II / 2
Protection degree	IP 20
Connection terminal	4 mm ² / 10 mm ²
Housing material	aluminium
Dimensions (LxHxD)	80x127x139 mm
Approximate weight	1.2 Kg
Mounting information	vertical on a rail, 10 mm from adjacent components
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
Marking tag	TAP207A, TAP128A, TAP178A, TAP209A
APPROVALS AND MARKINGS	CE,



- * 3-phase 400-500 Vac input or 2-phase with derating
- * Short circuit, overload, input and output overvoltage protections
- * Over temperature protection
- * Suitable for applications that require high reliability and performance
- * Smart alarm contact, signals when output voltage drops more than 10%
- * High overload capability to ensure the protections selectivity and start-up of heavy loads

1 Please refer to the datasheet for more details

2 Above overcurrent limit, the protection starts cycling in ON/OFF mode(hiccup autoreset), the maximum current supplied depends by the line resistance

PRODUCT DESCRIPTION

CSG960G 3-phase power supply input 400-500Vac / output 72Vdc 13.3A