


Single-phase
power supply input 120-230Vac / output 24Vdc 3A



Series	Easy Power
Code	XCSL1072W024VAA
Type	CSL1-072W/024V/AA
HS code	85044083
INPUT TECHNICAL DATA	
Input rated voltage	120–230 Vac
Input voltage AC	85...264 Vac
Input voltage DC	100...370 Vdc (derating Uin)
Frequency	47...63 Hz
Current consumption	0.8 A (120 Vac) / 0.4 A (230 Vac)
Inrush peak current	20 A
Power factor	> 0.65
Internal protection fuse	T 2 A
External protection on AC line	MT: C-4 A / Fuse: T 4 A
OUTPUT TECHNICAL DATA	
Output voltage range	24 Vdc
Output adjustable range	16 ... 28 Vdc
Continuous current	3 A at 50°C
Overload limiting	6 A for >30 s
Short circuit peak current	15 A for 50 ms
Ripple @ nominal ratings	40 mVpp
Hold up time	20 ms (120 Vac) / 70 ms (230 Vac)
Status indication	LED "DC OK"
Alarm contact	dry contact, max. 1A @ 24 Vdc (Uout >22.0 Vdc)
Parallel connection	possible
Redundant parallel connection	possible with external ORing diode
GENERAL TECHNICAL DATA	
Efficiency	87% (120 Vac) / 87% (230 Vac)
Dissipated power	10.8 W (120 Vac) / 10.8 W (230 Vac)
Operating temperature range	-20...+70°C (derating -3 W/°C >50°C)
Input / output isolation	3 kVac / 60 s (SELV output)
Input / ground isolation	1.5 kVac / 60 s
Output / ground isolation	0.5 kVac / 60 s
Safety Standard	EN 62368-1
EMC Standard	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4
Overvoltage category / pollution degree	II / 2
Protection degree	IP 20
Connection terminal	2.5 mm ² / 2.5 mm ²
Housing material	aluminium
Dimensions (LxHxD)	40x115x115 mm
Approximate weight	400 g
Mounting information	vertical on a rail, 20 mm from adjacent components
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
APPROVALS AND MARKINGS	
	CE, RoHS



- * Single phase and DC input
- * Short circuit, overload, input and output overvoltage protections
- * Over temperature protection
- * Suitable for standard applications
- * Alarm contact

1 Please refer to the datasheet for more details
2 Above overcurrent limit, the protection starts cycling in ON/OFF mode(hiccup autoreset), the maximum current supplied depends by the line resistance

PRODUCT DESCRIPTION

CSL1-072W/024V/AA Single-phase power supply input
120-230Vac / output 24Vdc 3A