




Power supply input 1x 230Vac/2x  
400-500Vac / output 24Vdc 40A

<b>Series</b>	Universal Power
<b>Code</b>	XCSW960CP
<b>Type</b>	CSW960CP
<b>HS code</b>	85044083
<b>INPUT TECHNICAL DATA</b>	
<b>Input rated voltage</b>	1x 230 Vac / 2x 400-500 Vac
<b>Input voltage AC</b>	180...264 Vac / 360...550 Vac (1)
<b>Input voltage DC</b>	550...775 Vdc
<b>Frequency</b>	47...63 Hz
<b>Current consumption</b>	4.7A (230 Vac) / 4A A (400 Vac)
<b>Inrush peak current</b>	16 A
<b>Power factor</b>	> 0.6
<b>External protection on AC line</b>	MT: C-10 A / Fuse: 1-2x T 10 A
<b>OUTPUT TECHNICAL DATA</b>	
<b>Output voltage range</b>	24 Vdc ±1%
<b>Output adjustable range</b>	23...27.5 Vdc
<b>Continuous current</b>	40 A a 45°C
<b>Overload limiting</b>	50 A for >5 s
<b>Short circuit peak current</b>	65 A for 5 s
<b>Ripple @ nominal ratings</b>	200 mVpp
<b>Hold up time</b>	20 ms (230 Vac) / 20 ms (400 Vac)
<b>Status indication</b>	LED "DC OK" / LED "Alarm"
<b>Alarm contact</b>	dry contact, max. 1A
<b>Parallel connection</b>	possible
<b>Redundant parallel connection</b>	already fitted with internal ORing diode
<b>GENERAL TECHNICAL DATA</b>	
<b>Efficiency</b>	90% (400 Vac) at 230 Vac
<b>Dissipated power</b>	<100 W (400 Vac) at 230 Vac
<b>Operating temperature range</b>	-20...+60°C (derating -32 W >45°C)
<b>Input / output isolation</b>	3 kVac / 60 s (SELV output)
<b>Input / ground isolation</b>	2 kVac / 60 s
<b>Output / ground isolation</b>	0.5 kVac / 60 s
<b>Standard / approvals</b>	EN 60950-1
<b>EMC Standard</b>	EN 61000-6-2, EN 61000-6-4
<b>Overvoltage category / pollution degree</b>	II / 2
<b>Protection degree</b>	IP 20
<b>Connection terminal</b>	4 mm <sup>2</sup> / 10 mm <sup>2</sup>
<b>Housing material</b>	aluminium
<b>Dimensions (LxHxD)</b>	80x139x127 mm
<b>Approximate weight</b>	1.2 Kg
<b>Mounting information</b>	vertical on a rail, 10 mm from adjacent components
<b>ACCESSORIES</b>	
<b>Mounting rail (IEC60715/TH35-7.5)</b>	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
<b>Mounting rail (IEC60715/TH35-15)</b>	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
<b>Marking tag</b>	TAP207A, TAP128A, TAP178A, TAP209A
<b>APPROVALS AND MARKINGS</b>	CE,



\* Single phase and two-phase input 185...480 Vac\* Short circuit, overload, input and output overvoltage protections\* Over temperature protection\* Suitable for applications that require high reliability and performance\* Smart alarm contact, signals when output voltage drops more than 10%\* High overload capability to ensure the protections selectivity and start-up of heavy loads  
1 Please refer to the datasheet for more details2 Above overcurrent limit, the protection starts cycling in ON/OFF mode(hiccup autoreset), the maximum current supplied depends by the line resistance3 (1) Dual voltage with selection through external jumper

## DESCRIZIONE DEL PRODOTTO

CSW960CP Power  
supply input 1x 230Vac/2x 400-500Vac / output 24Vdc 40A