





Single-phase
EMI filter 1 stage 3A 115–250Vac

Code	XF03DKBG5B
Type	F03DKBG5B (1)
HS code	85363010
GENERAL TECHNICAL DATA	
Rated voltage	115–250 Vac ± 10%
Continuous current	3 A
Leakage current	0.40 mA (115 Vac) / 0.80 mA (250 Vac)
Frequency	50...60 Hz
Operating temperature range	-25...+100°C
Isolation L / L	1.45 kVdc / 60 s (2)
Isolation L / PE	2.25 kVdc / 60 s (2)
Protection degree	IP 00
Connection terminal	flat plug (from 3 to 20 A) / self-blocking nut (30 A)
Housing material	metallic
Dimensions (LxHxD)	64.5x34x30 mm
Approximate weight	
Mounting information	screw fixing, on metal panel
Common mode (L/PE) attenuation (dB)	
0.15 MHz	20
0.5 MHz	30
1 MHz	35
5 MHz	45
10 MHz	50
30 MHz	45
Differential mode (L/PE) attenuation (dB)	
0.15 MHz	7
0.5 MHz	35
1 MHz	50
5 MHz	45
10 MHz	45
30 MHz	45
ACCESSORIES	
APPROVALS AND MARKINGS	  



- * Models from 3 to 30 A
- * Elevated attenuation from 150 kHz to 30 MHz
- * Elevated attenuation even on long cables
- * Compact dimension

- 1 (1) Produced on demand, contact our sales office for availability
- 2 (2) Isolation test need to be made in DC voltage, according to EN 60950, cause by the internal filter capacitors.

PRODUCT DESCRIPTION

F03DKBG5B Single-phase EMI
filter 1 stage 3A 115–250Vac