



Single-phase

EMI filter 2 stages 3A 115–250Vac

<b>Code</b>	XF03DPCG5C
<b>Type</b>	F03DPCG5C (1)
<b>HS code</b>	85363010
<b>GENERAL TECHNICAL DATA</b>	
<b>Rated voltage</b>	115–250 Vac $\pm$ 10%
<b>Continuous current</b>	3 A
<b>Leakage current</b>	0.40 mA (115 Vac) / 0.80 mA (250 Vac)
<b>Frequency</b>	50...60 Hz
<b>Operating temperature range</b>	-25...+100°C
<b>Isolation L / L</b>	1.45 kVdc / 60 s (2)
<b>Isolation L / PE</b>	2.25 kVdc / 60 s (2)
<b>Protection degree</b>	IP 00
<b>Connection terminal</b>	flat plug (from 3 to 20 A) / self-blocking nut (30 A)
<b>Housing material</b>	metallic
<b>Dimensions (LxHxD)</b>	45.5x71.5x30 mm
<b>Approximate weight</b>	
<b>Mounting information</b>	screw fixing, on metal panel
<b>Common mode (L/PE) attenuation (dB)</b>	
0.15 MHz	45
0.5 MHz	60
1 MHz	60
5 MHz	55
10 MHz	45
30 MHz	45
<b>Differential mode (L/PE) attenuation (dB)</b>	
0.15 MHz	12
0.5 MHz	45
1 MHz	45
5 MHz	45
10 MHz	45
30 MHz	45
<b>ACCESSORIES</b>	
<b>APPROVALS AND MARKINGS</b>	 , 



- \* Models from 3 to 30 A
- \* Elevated attenuation from 150 kHz to 30 MHz
- \* Elevated attenuation even on long cables
- \* Compact dimension

- 1 (1) Produced on demand, contact our sales office for availability
- 2 (2) Isolation test need to be made in DC voltage, according to EN 60950, cause by the internal filter capacitors.

## PRODUCT DESCRIPTION

F03DPCG5C Single-phase EMI filter 2 stages 3A 115–250Vac