


3-phase EMI filter with neutral 10A 440Vac

Series	TY
Code	XF10TYG9
Type	F10TYG9 (1)
HS code	85363010
GENERAL TECHNICAL DATA	
Rated voltage	440 Vac ± 10%
Continuous current	10 A
Leakage current	0.5 mA
Frequency	50...60 Hz
Operating temperature range	-25...+85°C
Isolation L / L	1.45 kVdc / 60 s (2)
Isolation L / PE	2.25 kVdc / 60 s (2)
Protection degree	IP 00
Connection terminal	flat plug (10 A) and screw (20 A)
Housing material	metallic
Dimensions (LxHxD)	50x85x44mm
Approximate weight	
Mounting information	screw fixing, on metal panel
Common mode (L/PE) attenuation (dB)	
0.15 MHz	10
0.5 MHz	20
1 MHz	20
5 MHz	20
10 MHz	30
30 MHz	25
Differential mode (L/PE) attenuation (dB)	
0.15 MHz	10
0.5 MHz	20
1 MHz	25
5 MHz	25
10 MHz	30
30 MHz	30
ACCESSORIES	
APPROVALS AND MARKINGS	



- * Models from 10 to 20 A
- * Elevated attenuation from 150 kHz to 30 MHz
- * Elevated attenuation even on long cables
- * Excellent quality/price/performance ratio

- 1 (1) Produced on demand, contact our sales office for availability
- 2 (2) Isolation test need to be made in DC voltage, according to EN 60950, cause by the internal filter capacitors.

PRODUCT DESCRIPTION

F10TYG9 3-phase EMI filter with neutral 10A 440Vac