



## IDC interface 26 poles male with LED

<b>Series</b>	IF
<b>Code</b>	XIF26PML
<b>Type</b>	IF26PML
<b>HS code</b>	85369010
<b>GENERAL TECHNICAL DATA</b>	
<b>Number of poles</b>	26
<b>Version</b>	IDC male
<b>Input rated voltage</b>	0...50 Vac/dc
<b>Input rated current</b>	750 mA max
<b>Operating temperature range</b>	-20...+60°C
<b>Overvoltage category / pollution degree</b>	II / 2
<b>Protection degree</b>	IP 00
<b>Connection terminal</b>	2.5 mm <sup>2</sup> screw
<b>Status indication</b>	LED (1)
<b>Dimensions (LxHxD)</b>	86x66x93 mm
<b>Housing material</b>	UL94V-0 plastic material
<b>Mounting information</b>	vertical on rails, side by side
<b>ACCESSORIES</b>	
<b>Mounting rail (IEC60715/TH35-7.5)</b>	PR003, PR903, PR005, PR927
<b>Mounting rail (IEC60715/TH35-15)</b>	PR007, PR907, PR006, PR928
<b>APPROVALS AND MARKINGS</b>	CE



\* Universal module

- 1 The terminal number corresponds to the connector number
- 2 (1) Status LEDs are configured for a nominal voltage of 24 Vdc and negative common

## PRODUCT DESCRIPTION

IF26PML IDC interface 26 poles male with LED