



## RJ45 panel plug RJ45 with connector

|                                    |  |
|------------------------------------|--|
| <b>Code</b>                        | XPSRJ45M00AA   |
| <b>Type</b>                        | PSP-RJ45/M00/AA  |
| <b>HS code</b>                     | 8536700099   |
| <b>GENERAL TECHNICAL DATA</b>      |  |
| <b>Type of connection outside</b>  | RJ45 connector   |
| <b>Type of connection inside</b>   | RJ45 connector   |
| <b>Contact surface</b>             | Gold over nickel                                       |
| <b>Plugging cycles</b>             | >750   |
| <b>Operating temperature range</b> | -25...+55°C  |
| <b>Safety Standard</b>             | IEC 62321-5:2013                                       |
| <b>Category</b>                    | RJ45 Cat.5   |
| <b>Protection degree</b>           | IP65 with rubber cap closed                            |
| <b>Housing material</b>            | Aluminium  |
| <b>Dimension</b>                   | 38.2mm M22   |
| <b>Approximate weight</b>          | 22 g   |
| <b>Mounting information</b>        | On panel with hole diameter 22mm, thickness 1...10 mm  |
| <b>Fixing</b>                      | Fixing with threaded ring on the back (without screws) |
| <b>APPROVALS AND MARKINGS</b>      | CE   |
| <b>ACCESSORIES</b>                 |  |
| <b>Ricambi</b>                     | Rubber cap code XPSPCAP1                               |



## PRODUCT DESCRIPTION

PSP-RJ45/M00/AA RJ45 panel plug RJ45 with connector