




10/100Mbps fast ethernet switch 8-RJ45, unmanaged

| | |
|---|--|
| Series | SWE-F |
| Code | XSWEF08PU |
| Type | SWE-F-08PU |
| HS code | 85176200 |
| Version | 8 – RJ45 unmanaged |
| Interface | |
| Number and type of interface | 8 RJ45 ports |
| Connection method | Auto negotiation and auto crossing |
| Transmission speed | 10/100 Mbps |
| MAC table size | 1 K |
| Status indication | Power, Link/Speed, Link /Activity |
| GENERAL TECHNICAL DATA | |
| Power supply voltage | 9...58 Vdc |
| Current consumption | <170 mA |
| Operating temperature range | -40...+60°C |
| Ambient temperature range | -40...+85°C |
| Standards | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az |
| Safety Standard | EN 62368-1 |
| EMC Standard | EN/IEC 61000-3-2; EN61000-3-3 |
| Overvoltage category /pollution degree | I / 2 |
| Protection degree | IP20 |
| Connection type | 1.5 mm ² (screw) |
| Housing material | metallic |
| Dimensions (LxHxD) | 42x141x98 mm |
| Approximate weight | 420 g |
| Mounting information | on a rail, side by side |
| APPROVALS AND MARKINGS | |
| CE | |
| ACCESSORIES | |
| Mounting rail (IEC60715/TH35-7.5) | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| Mounting rail (IEC60715/TH35-15) | PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB |



PRODUCT DESCRIPTION

SWE-F-08PU 10/100Mbps fast ethernet switch 8-RJ45, unmanaged